

This Page Is Inserted by IFW Operations  
and is not a part of the Official Record

## **BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning documents *will not* correct images,  
please do not report the images to the  
Image Problem Mailbox.**



(19)

(11) Publication number:



Generated Document.

## PATENT ABSTRACTS OF JAPAN

(21) Application number: 06297823

(51) Intl. Cl.: F24F 7/06

(22) Application date: 20.09.94

(30) Priority:	(71) Applicant: DAIKOKU DENKI CO. LTD.
(43) Date of application publication: 02.04.96	(72) Inventor: HAYASHI MELJI OZAKI NAOTO
(84) Designated contracting states:	(74) Representative:

(54) AIR BLOWING UNIT

(57) Abstract:

PURPOSE: To obtain an air blowing unit which can eliminate the smell sticking to an air receiving body and give it a feeling of substantial refreshment by blowing refreshing air against it.

CONSTITUTION: In an air blowing unit 1, external air is taken in from inlets 8 by air sending means 9 provided in the main body 2 of the unit and is passed through electrostatic type dust collectors 10 and deodorizing devices 11 and blown against the whole body of a user W from each air flow blowing part 14. Since an air flow is given fragrance by a fragrance producing part 12 and then blown evenly against the user W after it is cleaned and deodorized by the dust collectors 10 and the deodorizing devices 11, an excellent feeling of refreshment is attained, while the smell sticking to clothes and others is masked or neutralized by a constituent of

fragrance transferred onto the user W, and thus an excellent refreshing effect is obtained. Besides, a sound wave for silencing having a phase reverse to the one of a noise produced from the main body 2 of the unit is generated from a speaker 80 and superposed on the noise so that this be silenced.

COPYRIGHT: (C)1996,JPO

